

# Steel Sheet, Plate, Slab and Coil

Safety Data Sheet (SDS)

#### Section 1 – Identification

1(a) Product Identifier used on Label: Steel Sheet, Plate, Slab and Coil

1(b) Other means of identification: SSAB - 001

1(c) Recommended use of the chemical and restrictions on use: Structural steel for sustainable & lightweight solutions, Wear plate for maximum payload & longer service life, Cold rolled steel for lightweight & safe components, Structural steel for heavy & demanding applications, Pre-painted steel for sustainable & durable buildings, Protection plate for the safety of life & property, Ready-to-use engineering & tool steel for saving time to market."

1(d) Name, address, and telephone number:

SSAB Americas Phone: (251) 662-4400 (8:00 am to 5:00 pm)

11 N. Water Street Suite 17000

Mobile, AL 36602

1(e) Emergency Phone Number: (563) 381-5311 (after 5:00pm, weekends, holidays)

#### Section 2 – Hazard(s) Identification

2(a) Classification of the chemical: Steel Sheet, Plate, Slab and Coil is considered an article under Reach regulation (REACH REGULATION (EC) No 1907/2006) and is not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008). However, Steel Sheet, Plate, Slab and Coil are not exempt as an article under OSHA's Hazard Communication Standard (29 CFR 1910.1200) due to its downstream use, thus this product is considered a mixture and a hazardous material. Therefore, the categories of Health Hazards as defined in "GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS), Third revised edition ST/SG/AC.10/30/Rev. 3" United Nations, New York and Geneva, 2009 have been evaluated. Refer to Section 3, 8 and 11 for additional information.

2(b) Signal word, hazard statement(s), symbols and precautionary statement(s):

Hazard Symbol	Hazard Classification	Signal Word	Hazard Statement(s)
	Carcinogenicity - 2		Suspected of causing cancer.
	Reproductive Toxicity - 2		Suspected of damaging fertility or the unborn child.
No.	Single Target Organ Toxicity (STOT) Repeat Exposure - 1		Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure.
	Acute Toxicity-Oral - 4	DANGER	Harmful if swallowed.
	Skin Sensitization - 1		May cause an allergic skin reaction.
~	STOT Single Exposure - 3	Harmful in contact with skin.	
NT A	E 1 '' (' OD	-	May cause respiratory irritation.
NA	Eye Irritation - 2B		Causes eye irritation.

#### Precautionary Statement(s):

Wear protective gloves / protective clothing / eye protection /	Response  Remove person to fresh air and keep comfortable for breathing.  xposed, concerned or feel unwell: Get medical advice/attention.	Storage/Disposal
Wear protective gloves / protective clothing / eye protection / face protection.	breathing.  xposed, concerned or feel unwell: Get medical	
1 0	•	
	advice/attention.	
	es: Rinse cautiously with water for several minutes. contact lenses, if present and easy to do. Continue Rinsing.	Dispose of contents in accordance with federal, state and local regulations.
Obtain special instructions before use.  Do not handle until all safety precautions have been read and understood.  If on skin: Get medic	Wash with plenty of water. If irritation or rash occurs: cal advice/attention. Take off and wash contaminated clothing before reuse.  Call a poison center/doctor if you feel unwell.	

2(c) Hazards not otherwise classified: None Known

2(d) Unknown acute toxicity statement (mixture): None Known

#### Section 3 – Composition/Information on Ingrédients

# 3(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration:

CAS Number	EC Number	% weight *	
7439-89-6	231-096-4	99.8	
7440-47-3	231-157-5	3	
7439-96-5	231-105-1	2.2	
	7439-89-6 7440-47-3	7439-89-6 231-096-4 7440-47-3 231-157-5	



SSAB Code No.: SSAB-001 Safety Data Sheet (SDS) Revision: 10/31/2018

# Section 3 – Composition/Information on Ingrédients (continued)

3(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration (continued):

5(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration (continued):				
Chemical Name	CAS Number	EC Number	% weight *	
Nickel	7440-02-0	231-111-4	2.0	
Carbon	7440-44-0	231-153-3	1	
Copper	7440-50-8	231-159-6	1	
Silicon	7440-21-3	231-130-8	1	
Molybdenum	7439-9877	231-107-2	1	

EC - European Community

CAS - Chemical Abstract Service

- All commercial steel products contain small amounts of various elements in addition to those specified. These small quantities frequently referred to as "trace" or "residual" elements generally originate in the raw materials used and vary in concentration by weight, and may include: aluminum, titanium, vanadium, niobium, tin, sulfur, boron, and phosphorus.
- \* Element weight percentage shown represent concentrations possible over all product ranges. These do not represent actual steel specification limits for any SSAB steel grade produced.

#### Section 4 – First-aid Measures

#### 4(a) Description of necessary measures:

- Inhalation: Steel Sheet, Plate, Slab and Coil as sold/shipped is not a likely form of exposure. However, during further processing (welding, grinding, burning, etc.), if inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed, concerned or feel unwell: Get medical advice/attention.
- Eye Contact: Steel Sheet, Plate, Slab and Coil as sold/shipped is not a likely form of exposure. However, during further processing (welding, grinding, burning, etc.), if in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. If eye irritation persists: Get medical advice attention. If exposed, concerned or feel unwell: Get medical advice/attention.
- Skin Contact: If on skin: Wash thoroughly after handling. Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off and wash contaminated clothing before reuse. If exposed, concerned or feel unwell: Get medical advice/attention.
- Ingestion: Steel Sheet, Plate, Slab and Coil as sold/shipped is not a likely form of exposure. However, during further processing (welding, grinding, burning, etc.), if swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If exposed, concerned or feel unwell: Get medical advice/attention.

#### 4(b) Most important symptoms/effects, acute and delayed (chronic):

- Inhalation: Steel Sheet, Plate, Slab and Coil as sold/shipped is not likely to present an acute or chronic heath effect.
- Eye: Steel Sheet, Plate, Slab and Coil as sold/shipped is not likely to present an acute or chronic heath effect.
- Skin: Steel Sheet, Plate, Slab and Coil as sold/shipped is not likely to present an acute or chronic heath effect.
- Ingestion: Steel Sheet, Plate, Slab and Coil as sold/shipped is not likely to present an acute or chronic heath effect.

However, during further processing (welding, grinding, burning, etc.) individual components may illicit an acute or chronic heath effect. Refer to Section 11-Toxicological Information.

4(c) Immediate Medical Attention and Special Treatment: None Known

#### **Section 5 – Fire-fighting Measures**

- 5(a) Suitable (and unsuitable) Extinguishing Media: Not Applicable for Steel Sheet, Plate, Slab and Coil as sold/shipped. Use extinguishers appropriate for surrounding materials.
- 5(b) Specific Hazards arising from the chemical: Not Applicable for Steel Sheet, Plate, Slab and Coil as sold/shipped. When burned, toxic smoke, fume and vapor may be emitted.
- **5(c) Special protective equipment and precautions for fire-fighters:** Self-contained NIOSH approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

#### **Section 6 - Accidental Release Measures**

- **6(a) Personal Precautions, Protective Equipment and Emergency Procedures:** Not applicable to steel in solid state. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust. Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid using compressed air. Do not release into sewers or waterways. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations.
- **6(b) Methods and materials for containment and clean up:** Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations. Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal requirements.



SSAB Code No.: SSAB-001 Safety Data Sheet (SDS) Revision: 10/31/2018

# **Section 7 - Handling and Storage**

7(a) Precautions for safe handling: Not Applicable for Steel Sheet, Plate, Slab and Coil as sold/shipped, however further processing (welding, burning, grinding, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in well ventilated areas. Practice good housekeeping. Avoid breathing metal fumes and/or dust. Do not eat, drink or smoke when using this product. Cut resistant gloves and sleeves should be worn when working with steel products.

7(b) Conditions for safe storage, including any incompatibilities: Store away from acids and incompatible materials.

# **Section 8 - Exposure Controls / Personal Protection**

**8(a) Occupational Exposure Limits (OELs): Steel Sheet, Plate, Slab and Coil** as sold/shipped in its physical form does not present an inhalation, ingestion or contact hazard, nor would any of the following exposure data apply. However, operations such as burning, welding (high temperature), sawing, brazing, machining, grinding, etc. may produce fumes and/or particulates. The following exposure limits are offered as reference for an experienced industrial hygienist to review.

Ingredients	OSHA PEL <sup>1</sup>	ACGIH TLV <sup>2</sup>	NIOSH REL <sup>3</sup>	IDLH <sup>4</sup>
Iron	10 mg/m³ (iron oxide fume)	5.0 mg/m³ (iron oxide, respirable fraction <sup>5</sup> )	5.0 mg/m³ (iron oxide dust and fume)	2,500 mg/m <sup>3</sup> (as Fe)
1.0 mg/m³ (as Cr, metal)  0.005 mg/m³ (as Cr VI, inorganic compounds, water soluble & insoluble)  "AL" 0.0025 mg/m³ (as Cr VI, inorganic compounds, water soluble & insoluble)  "Solution of the soluble		0.003 mg/m³ (as Cr III, inorganic compounds, inhalable fraction6) "DSEN & RSEN" "water-soluble" compounds only 0.5 mg/m³ (as Cr, metal, inhalable fraction) 0.0002 mg/m³ (as Cr VI, inorganic compounds, water insoluble & insoluble) "STEL" 0.0005 mg/m³ (as Cr VI, inorganic compounds, water insoluble & insoluble)	0.5 mg/m³ (as Cr II & III, inorganic compounds & metal) 0.0002 mg/m³ (as Cr VI, inorganic compounds, water insoluble & insoluble)	250 mg/m³ (as Cr II & metal) 25 mg/m³ (as Cr III) 15 mg/m³ (as Cr VI, Ca)
Manganese	"C" 5.0 mg/m³ (as fume & inorganic compounds, as Mn)	0.02 mg/m³ (as fume & inorganic compounds, as Mn, respirable fraction) 0.1 mg/m³ (as fume & inorganic compounds, as Mn, inhalable fraction)	1.0 mg/m³ (as fume & inorganic compounds, as Mn) "STEL" 3.0 mg/m³ (as fume & inorganic compounds, as Mn)	500 mg/m <sup>3</sup> (as Mn)
Nickel	1.0 mg/m³ (metal, insoluble & soluble compounds, as Ni)	1.5 mg/m³ (metal, as Ni, as inhalable fraction)  0.2 mg/m³ (insoluble compounds, as Ni, inhalable fraction, inorganic only)  0.1 mg/m³ (soluble compounds, as Ni, inhalable fraction, inorganic only)	0.015 mg/m³ (metal & insoluble and soluble compounds, as Ni)	10 mg/m³ (as Ni)
Carbon	15 mg/m³ (as total dust, PNOR <sup>7</sup> ) 5.0 mg/m³ (as respirable fraction, PNOR)	10 mg/m³ (as inhalable fraction, PNOS <sup>8</sup> ) 3.0 mg/m³ (as respirable fraction, PNOS)	NE	NE
Copper 0.1 mg/m³ (as fume, Cu) 1.0 mg/m³ (as dusts & mists, Cu)		0.2 mg/m³ (as fume) 1.0 mg/m³ (as dusts & mists, Cu)	0.1 mg/m³ (as fume, Cu) 1.0 mg/m³ (as dusts & mists, Cu)	100 mg Cu/m <sup>3</sup>
Silicon	15 mg/m³ (total dust, PNOR) 5.0 mg/m³ (as respirable fraction, PNOR)	10 mg/m³	10 mg/m³ (as total dust) 5.0 mg/m³ (as respirable dust)	NE
Molybdenum	15 mg/m³ (as total dust, PNOR) 5.0 mg/m³ (as respirable fraction, PNOR)	10 mg/m³ (as Mo insoluble compounds, inhalable fraction) 3.0 mg/m³ (as Mo insoluble compounds, respirable fraction) 0.5 mg/m³ (as Mo soluble compounds, respirable fraction)	NE	NE

#### NE - None Established

- 1. OSHA Permissible Exposure Limits (PELs) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A (C) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Peak is defined as the acceptable maximum peak for a maximum duration above the ceiling concentration for an eight-hour shift. A skin notation refers to the potential significant contribution to the overall exposure by the cutaneous route, either by contact with vapors or, of probable greater significance, by direct skin contact with the substance. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday. An Action level (AL) is used by OSHA and NIOSH to express a health or physical hazard. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.
- 2. Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as the maximum concentration to which workers can be exposed for a short period of time (15 minutes) for only four times throughout the day with at least one hour between exposures. A "skin" notation refers to the potential significant contribution to the overall exposure by the cutaneous route, either by contact with vapors or, of probable greater significance, by direct skin contact with the substance. DSEN May cause dermal sensitization. This notation is used to indicate the potential for dermal sensitization resulting from the interaction of an absorbed agent and ultraviolet light (i.e. photosensitization). RSEN May cause respiratory sensitization.
- 3. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL)- Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
- 4. The "immediately dangerous to life or health air concentration values (IDLHs)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994. Ca is designated as carcinogen.



SSAB Code No.: SSAB-001 Safety Data Sheet (SDS) Revision: 10/31/2018

# **Section 8 - Exposure Controls / Personal Protection (continued)**

#### **8(a) Occupational Exposure Limits (OELs) (continued):**

- 5. Respirable fraction. The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in ACGIH 2018 TLVs ® and BEIs ® Appendix D, paragraph C.
- 6. Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH 2018 TLVs \*\* and BEIs \*\* (Biological Exposure Indices) Appendix D, paragraph A.
- 7. PNOR (Particulates Not Otherwise Regulated). All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by a limit which is the same as the inert or nuisance dust limit of 15 mg/m³ for total dust and 5.0 mg/m³ for the respirable fraction.
- 8. PNOS (Particulates Not Otherwise Specified). Particulates identified under the PNOS heading are "nuisance dusts" containing no asbestos and <1% crystalline silica.

**8(b) Appropriate Engineering Controls:** Use controls as appropriate to minimize exposure to metal fumes and dusts during handling operations. Provide general or local exhaust ventilation systems to minimize airborne concentrations. Local exhaust is necessary for use in enclosed or confined spaces. Provide sufficient general/local exhaust ventilation in pattern/volume to control inhalation exposures below current exposure limits.

#### 8(c) Individual Protection Measures:

• Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (Immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure and powered-air do not protect workers in oxygen-deficient atmospheres.

- Eyes: Wear appropriate eye protection to prevent eye contact. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use safety glasses to prevent eye contact. Contact lenses should not be worn where industrial exposures to this material are likely. Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding or machining operations.
- Skin: Wear appropriate personal protective clothing to prevent skin contact. Cut resistant gloves and sleeves should be worn when working with steel products. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use protective clothing, and gloves to prevent skin contact. Protective gloves should be worn as required for welding, burning or handling operations. Contaminated work clothing must not be allowed out of the workplace.
- Other protective equipment: An eyewash fountain and deluge shower should be readily available in the work area.

#### **Section 9 - Physical and Chemical Properties**

9(a) Appearance (physical state, color, etc.): Solid, Black Gray

9(b) Odor: Odorless 9(c) Odor Threshold: NA

9(d) pH: NA

**9(e) Melting Point/Freezing Point:** 1530°C (2786°F)

9(f) Initial Boiling Point and Boiling Range: 2900°C (5252°F)

9(g) Flash Point: NA9(h) Evaporation Rate: NA

9(i) Flammability (solid, gas): Non-flammable, non-combustible

NA - Not Applicable

 $\boldsymbol{N}\boldsymbol{D}$  - Not Determined for product as a whole

9(j) Upper/lower Flammability or Explosive Limits: NA

9(k) Vapor Pressure: NA9(l) Vapor Density (Air = 1): NA9(m) Relative Density: 7.86

9(n) Solubility(ies): Water Insoluble

9(o) Partition Coefficient n-octanol/water: ND

9(p) Auto-ignition Temperature: NA9(q) Decomposition Temperature: ND

9(r) Viscosity: NA

# Section 10 - Stability and Reactivity

10(a) Reactivity: Not Determined (ND) for product in a solid form. Do not use water on molten metal.

10(b) Chemical Stability: Steel products are stable under normal storage and handling conditions.

10(c) Possibility of hazardous reaction: None Known

10(d) Conditions to Avoid: Storage with strong acids or calcium hypochlorite

10(e) Incompatible Materials: Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.

**10(f) Hazardous Decomposition Products:** Thermal oxidative decomposition of steel products can produce fumes containing oxides of iron and manganese as well as other alloying elements.



SSAB Code No.: SSAB-001 Safety Data Sheet (SDS) Revision: 10/31/2018

# **Section 11 - Toxicological Information**

11(a-e) Information on toxicological effects: The following toxicity data has been determined for Steel Sheet, Plate, Slab and Coil when further processed using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of OSHA and the EU CPL:

Hazard Classification	Hazard Category		Hazard Signal	Hazard Statement		
Hazard Classification	EU	OSHA	Symbols Word		Hazaru Statement	
<b>Acute Toxicity Hazard</b> (covers Categories 1-4)	NA*	4 <sup>a</sup>	<b>(1)</b>	Warning	Harmful if swallowed.	
Eye Damage/ Irritation (covers Categories 1, 2A and 2B)	NA*	2B°	No Pictogram	Warning	Causes eye irritation.	
<b>Skin/Dermal Sensitization</b> (covers Category 1)	NA*	1 <sup>d</sup>	<b>(1)</b>	Warning	May cause an allergic skin reaction.	
Carcinogenicity (covers Categories 1A, 1B and 2)	NA*	2 <sup>g</sup>		Warning	Suspected of causing cancer.	
<b>Toxic Reproduction</b> (covers Categories 1A, 1B and 2)	NA*	2 <sup>h</sup>		Warning	Suspected of damaging fertility or the unborn child.	
Specific Target Organ Toxicity (STOT) Following Single Exposure (covers Categories 1-3)	NA*	3 <sup>i</sup>	<b>(1)</b>	Warning	May cause respiratory irritation.	
STOT following Repeated Exposure (covers Categories 1 and 2)	NA*	1 <sup>j</sup>		Danger	Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure.	

<sup>\*</sup> Not Applicable - Semi-formed steel products are considered articles under Reach regulation (REACH REGULATION (EC) No 1907/2006) and are not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008).

Toxicological data listed below are presented regardless to classification criteria. Individual hazard classification categories where the toxicological information has met or exceeded a classification criteria threshold are listed above.

- a. No  $LC_{50}$  or  $LD_{50}$  has been established for **Steel Sheet**, **Plate**, **Slab and Coil**. The following data has been determined for the components:
  - **Iron:** Rat LD<sub>50</sub> =98.6 g/kg (REACH)

Rat  $LD_{50} = 1060 \text{ mg/kg (IUCLID)}$ 

Rat LD<sub>50</sub> =984 mg/kg (IUCLID)

Rabbit LD<sub>50</sub> =890 mg/kg (IUCLID)

Guinea Pig LD<sub>50</sub> =20 g/kg (TOXNET)

• Silicon:  $L_{D50} = 3160 \text{ mg/kg (Oral/Rat)}$ 

• **Carbon:** LD<sub>50</sub>= >10,000 mg/kg (Oral/ Rat)

• Copper: Rat  $LD_{50} = 481 \text{ mg/kg}$  (REACH)

Rat LD<sub>50</sub> > 2500 mg/kg (REACH)

• Manganese: Rat LD<sub>50</sub> > 2000 mg/kg (REACH)

Rat LD<sub>50</sub> > 9000 mg/kg (NLM Toxnet)

• **Nickel:** LD<sub>50</sub> >9000 mg/kg (Oral/Rat)

- b. No Skin (Dermal) Irritation data available for **Steel Sheet, Plate, Slab and Coil** as a as a mixture. The following Skin (Dermal) Irritation information was found for the components:
  - Molybdenum: May cause skin irritation.
- c. No Eye Irritation data available for **Steel Sheet, Plate, Slab and Coil** as a mixture. The following Eye Irritation information was found for the components:
  - Iron and Molybdenum: Causes eye irritation.
  - Silicon: Slight eye irritation in rabbit protocol.
  - Nickel: Slight eye irritation from particulate abrasion only.
- d. No Skin (Dermal) Sensitization data available for **Steel Sheet, Plate, Slab and Coil** as a mixture. The following Skin (Dermal) Sensitization information was found for the components:
  - Nickel: May cause allergic skin sensitization
- e. No Respiratory Sensitization data available for Steel Sheet, Plate, Slab and Coil as a mixture or its components.
- f. No Germ Cell Mutagenicity data available for **Steel Sheet, Plate, Slab and Coil** as a mixture. The following Mutagenicity and Genotoxicity information was found for the components:
  - Iron: IUCLID has found some positive and negative findings in vitro.
  - Nickel: EU RAR has found positive results in vitro and in vivo but insufficient data for classification.
- g. Carcinogenicity: IARC, NTP, and OSHA do not list **Steel Sheet, Plate, Slab and Coil** as carcinogens. The following Carcinogenicity information was found for the components:
  - Nickel and certain nickel compounds IARC-1 (compounds), carcinogen to humans; IARC-2B (elemental & alloys), possibly carcinogenic to humans; ACGIH TLV-A1 (insoluble compounds, as Ni), confirmed human carcinogen; TLV-A5 (elemental), not suspected as a human carcinogen; NTP-K, known to be a carcinogen; NIOSH-Ca, potential occupational carcinogen.
  - Welding Fumes IARC-2B, possibly carcinogenic to humans; NIOSH-Ca, potential occupational carcinogen.



Safety Data Sheet (SDS) Revision: 10/31/2018

# **Section 11 - Toxicological Information (continued)**

#### 11(a-e) Information on toxicological effects (continued):

- h. Carcinogenicity (continued):
  - Chromium (as metal and trivalent chromium compounds) IARC-3 (organic & inorganic compounds), unclassifiable as to carcinogenicity in humans; ACGIH TLV-A4, not classifiable as a human carcinogen; EPA-D, not classifiable as to human carcinogenicity (CBD, cannot be determined).
  - Chromium (hexavalent) IARC-1, carcinogen to humans; ACGIH TLV-A1, confirmed human carcinogen; NIOSH-Ca, potential occupational carcinogen; NTP-K, known to be a carcinogen; EPA-A, human carcinogen (by inhalation route of entry), EPA-K, cannot be determined, not classifiable as to human carcinogenicity.
- i. No Toxic Reproduction data available for **Steel Sheet, Plate, Slab and Coil** as a mixture. The following Toxic Reproductive information was found for the components:
  - · Nickel: Effects on fertility.
- j. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for **Steel Sheet, Plate, Slab and Coil** as a mixture. The following STOT following a Single Exposure data was found for the components:
  - Iron and Molybdenum: Irritating to Respiratory tract.
- k. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for **Steel Sheet, Plate, Slab and Coil** as a whole. The following STOT following Repeated Exposure data was found for the components:
  - Copper: Target organs affected Skin, eyes liver, kidneys and respiratory tract.
  - Nickel: Rat 4 wk inhalation LOEL 4 mg/m³ Lung and Lymph node histopathology. Rat 2 yr inhalation LOEL 0.1 mg/m³ Pigment in kidney, effects on hematopoiesis spleen and bone marrow and adrenal tumor. Rat 13 Week Inhalation LOAEC 1.0 mg/m³ Lung weights and Alveolar histopathology.
  - Manganese: Inhalation of metal fumes Degenerative changes in human Brain; Behavioral: Changes in motor activity and muscle weakness (Whitlock et al., 1966).

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2018, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS).

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s) and potential resultant components from further processing:

#### **Acute Effects:**

- Inhalation: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract. Excessive inhalation of fumes of freshly formed metal oxide particles sized below 1.5 micrometer and usually between 0.02-0.05 micrometers from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms), metallic taste in the mouth, dryness and irritation of the throat followed by weakness and muscle pain. The symptoms come on in a few hours after excessive exposures and usually last from 12 to 48 hours. Long-term effects from metal fume fever have not been noted. Freshly formed oxide fumes of manganese and copper have been associated with causing metal fume fever.
- Eye: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes.
- Skin: Skin contact with metal dusts may cause irritation or sensitization, possibly leading to dermatitis. Skin contact with metallic fumes and dusts may cause physical abrasion.
- Ingestion: Ingestion of harmful amounts of this product as distributed is unlikely due to its solid insoluble form. Ingestion of metal dust may cause nausea or vomiting.

#### Acute Effects by component:

- Iron and iron oxides: Iron is harmful if swallowed, causes skin irritation, and causes eye irritation. Contact with iron oxide has been reported to cause skin irritation and serious eye damage. Particles of iron or iron compounds, which become imbedded in the eye, may cause rust stains unless removed fairly promptly.
- Chromium, chromium oxides and hexavalent chrome: Hexavalent chrome causes damage to gastrointestinal tract, lung, severe skin burns and eye damage, serious eye damage, skin contact may cause an allergic skin reaction. Inhalation may cause allergic or asthmatic symptoms or breathing difficulties.
- Manganese and manganese oxides: Manganese and Manganese oxide are harmful if swallowed.
- Nickel and nickel oxides: Nickel may cause allergic skin sensitization. Nickel oxide may cause an allergic skin.
- Carbon: Not Reported/ Not Classified
- Copper and copper oxides: Copper may cause allergic skin reaction. Copper oxide is harmful if swallowed, causes skin and eye irritation, and may cause an allergic skin reaction.
- Silicon and silicon oxides: May be harmful if swallowed.
- Molybdenum and oxides: Molybdenum causes skin and eye irritation. Molybdenum oxide is toxic if swallowed, and causes eye irritation

#### Delayed (chronic) Effects by component:

• Iron and iron oxides: Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign pneumoconiosis, called siderosis, which is observable as an X-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. Iron oxide is listed as a Group 3 (not classifiable) carcinogen by IARC.



SSAB Code No.: SSAB-001 Safety Data Sheet (SDS) Revision: 10/31/2018

# **Section 11 - Toxicological Information (continued)**

#### **Delayed (chronic) Effects by component (continued):**

- Chromium, chromium oxides and hexavalent chromium: The health hazards associated with exposure to chromium are dependent upon its oxidation state. The metal form (chromium as it exists in this product) is of very low toxicity. The hexavalent form is very toxic. Repeated or prolonged exposure to hexavalent chromium compounds may cause respiratory irritation, nosebleed, ulceration and perforation of the nasal septum. Industrial exposure to certain forms of hexavalent chromium has been related to an increased incidence of cancer. NTP (The National Toxicology Program) Fourth Annual report on Carcinogens cites "certain Chromium compounds" as human carcinogens. ACGIH has reviewed the toxicity data and concluded that chromium metal is not classifiable as a human carcinogen. Hexavalent chromium may cause genetic defects and is suspected of damaging the unborn child. Developmental toxicity in the mouse, suspected of damaging fertility or the unborn child.
- Manganese and manganese oxides: Chronic exposure to high concentrations of manganese fumes and dusts may adversely affect the central nervous system with symptoms including languor, sleepiness, weakness, emotional disturbances, spastic gait, mask-like facial expression and paralysis. Animal studies indicate that manganese exposure may increase susceptibility to bacterial and viral infections. Occupational overexposure (Manganese) is a progressive, disabling neurological syndrome that typically begins with relatively mild symptoms and evolves to include altered gait, fine tremor, and sometimes, psychiatric disturbances. May cause damage to lungs with repeated or prolonged exposure. Neurobehavioral alterations in worker populations exposed to manganese oxides include: speed and coordination of motor function are especially impaired.
- Nickel and nickel oxides: Exposure to nickel dusts and fumes can cause sensitization dermatitis, respiratory irritation, asthma, pulmonary fibrosis, edema, and may cause nasal or lung cancer in humans. Nickel causes damage to lungs through prolonged or repeated inhalation exposure. IARC lists nickel and certain nickel compounds as Group 2B carcinogens (sufficient animal data). ACGIH 2018 TLVs® and BEIs® lists insoluble nickel compounds as confirmed human carcinogens. Nickel is suspected of damaging the unborn child.
- Carbon: Chronic inhalation may lead to decreased pulmonary function.
- Copper and copper oxides: Inhalation of high concentrations of freshly formed oxide fumes and dusts of copper can cause metal fume fever. Chronic inhalation of copper dust has caused, in animals, hemolysis of the red blood cells, deposition of hemofuscin in the liver and pancreas, injury to lung cells and gastrointestinal symptoms.
- Silicon and silicon oxides: Silicon dusts are a low health risk by inhalation and should be treated as a nuisance dust. Eye contact with pure material can cause particulate irritation. Skin contact with silicon dusts may cause physical abrasion.
- Molybdenum and oxides: Certain handling operations, such as burning and welding, may generate both insoluble molybdenum compounds (metal and molybdenum dioxide) and soluble molybdenum compounds (molybdenum trioxide). Molybdenum compounds generally exhibit a low order of toxicity with the trioxide the more toxic. However, some reports indicate that the dust of the molybdenum metal, molybdenum dioxide and molybdenum trioxide may cause eye, skin, nose and throat irritation in animals. Also, it has been reported to cause induction of tumors in experimental animals, suspected of causing cancer. Molybdenum oxide is suspected of causing cancer in humans.

# **Section 12 - Ecological Information**

12(a) Ecotoxicity (aquatic & terrestrial): No Data Available for Steel Sheet, Plate, Slab and Coil as sold/shipped. However, individual components of the product when processed have been found to be toxic to the environment. Metal dusts may migrate into soil and groundwater and be ingested by wildlife as follows:

- Iron Oxide: LC<sub>50</sub>: >1000 mg/L; Fish 48 h-EC<sub>50</sub> > 100 mg/L (Currenta, 2008k); 96 h-LC<sub>0</sub> ≥ 50,000 mg/L Test substance: Bayferrox 130 red (95 97% Fe<sub>2</sub>O<sub>3</sub>; < 4% SiO<sub>2</sub> and Al<sub>2</sub>O<sub>3</sub>) (Bayer, 1989a)
- Hexavalent Chrome: EU RAR listed as category 1, found acute EC50 and LD50 to algae and invertebrates < 1 mg.
- Nickel Oxide: IUCLID found LC<sub>50</sub> in fish, invertebrates and algae > 100 mg/l.
- 12(b) Persistence & Degradability: No Data Available for Steel Sheet, Plate, Slab and Coil as sold/shipped or individual components.
- 12(c) Bioaccumulative Potential: No Data Available for Steel Sheet, Plate, Slab and Coil as sold/shipped or individual components.
- 12(d) Mobility (in soil): No data available for Steel Sheet, Plate, Slab and Coil as sold/shipped. However, individual components of the product have been found to be absorbed by plants from soil.

12(e) Other adverse effects: None Known

Additional Information:

Hazard Category: Not Reported Signal Word: No Signal Word

**Hazard Symbol:** No Symbol **Hazard Statement:** No Statement

#### **Section 13 - Disposal Considerations**

**Disposal:** Steel scrap should be recycled whenever possible. Product dusts and fumes from processing operations should also be recycled or classified by a competent environmental professional and disposed of in accordance with applicable federal, state or local regulations.

**Container Cleaning and Disposal:** Follow applicable federal, state and local regulations. Observe safe handling precautions. European Waste Catalogue (EWC): 16-01-17 (ferrous metals), 12-01-99 (wastes not otherwise specified), 16-03-04 (off specification batches and unused products), or 15-01-04 (metallic packaging).

Please note this information is for Steel Sheet, Plate, Slab and Coil in its original form. Any alterations can void this information.



SSAB Code No.: SSAB-001 Safety Data Sheet (SDS) Revision: 10/31/2018

# **Section 14 - Transport Information**

#### 14 (a-g) Transportation Information:

**US Department of Transportation (DOT)** under 49 CFR 172.101 **does not** regulate **Steel Sheet, Plate, Slab and Coil** as a hazardous material. All federal, state, and local laws and regulations that apply to the transport of this type of material must be adhered to.

Shipping Name: Not Applicable (NA) **Packaging Authorizations Quantity Limitations** Shipping Symbols: NA a) Exceptions: NA a) Passenger, Aircraft, or Railcar: NA Hazard Class: NA b) Group: NA b) Cargo Aircraft Only: NA UN No.: NA c) Authorization: NA **Vessel Stowage Requirements** Packing Group: NA a) Vessel Stowage: NA DOT/IMO Label: NA b) Other: NA Special Provisions (172.102): NA **DOT Reportable Quantities:** NA

International Maritime Dangerous Goods (IMDG) and the Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID) classification, packaging and shipping requirements follow the US DOT Hazardous Materials Regulation.

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR) does not regulate Steel Sheet, Plate, Slab and Coil as a hazardous material.

Shipping Name: Not Applicable (NA)

Classification Code: NA

UN No.: NA

Packing Group: NA

ADR Label: NA

Special Provisions: NA

Limited Quantities: NA

Packaging

a) Packaging

a) Packaging

a) Packaging

a) Packaging

b) Special Instructions: NA

b) Special Provisions: NA

b) Special Provisions: NA

c) Mixed Packing Provisions: NA

Limited Quantities: NA

International Air Transport Association (IATA) does not regulate Steel Sheet, Plate, Slab and Coil as a hazardous material.

Shipping Name: Not Applicable (NA)	Passenger & 0	Passenger & Cargo Aircraft		<b>Special Provisions:</b>
Class/Division: NA	Limited Quantity (EQ)	Limited Quantity (EQ)		NA
Hazard Label (s): NA	Pkg Inst: NA	Pkg Inst: NA		
UN No.: NA			Max Net Qty/Pkg:	ERG Code: NA
Packing Group: NA	Max Net Qty/Pkg: NA	Max Net Qty/Pkg:	NA	
Excepted Quantities (EQ): NA	NA	NA		
Pkg Inst – Packing Instructions Max Net Qty/Pkg –	Maximum Net Quantity per Package		ERG - Emergency Resp	onse Drill Code

Transport Dangerous Goods (TDG) Classification: Steel Sheet, Plate, Slab and Coil does not have a TDG classification.

#### **Section 15 - Regulatory Information**

**Regulatory Information**: The following listing of regulations relating to an SSAB product may not be complete and should not be solely relied upon for all regulatory compliance responsibilities.

This product and/or its constituents are subject to the following regulations:

**OSHA Regulations:** Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-2, Z-3): The product, **Steel Sheet, Plate, Slab and Coil** as a whole is not listed. However, individual components of the product are listed: Refer to Section 8, Exposure Controls and Personal Protection

**EPA Regulations:** The product, **Steel Sheet, Plate, Slab and Coil** is not listed as a whole. However, individual components of the product are listed:

Components	Regulations	
Chromium	CERCLA, CWA, SARA 313, RCRA, SDWA,	
Manganese	CAA, SARA 313, SDWA	
Nickel	CAA, CERCLA, CWA, SARA 313	
Copper	CWA, SARA 313, SDWA	

# SARA 311/312 Potential Hazard Categories: Immediate Acute Health Hazard; Delayed Chronic Health Hazard Regulations Key:

- CAA Clean Air Act (42 USC Sec. 7412; 40 CFR Part 61 [As of: 8/18/06])
- CERCLA Comprehensive Environmental Response, Compensation and Liability Act (42 USC Secs. 9601(14), 9603(a); 40 CFR Sec. 302.4, Table 302.4, Table 302.4 and App. A)
  - CWA Clean Water Act (33 USC Secs. 1311; 1314(b), (c), (e), (g); 136(b), (c); 137(b), (c) [as of 8/2/06])
  - RCRA Resource Conservation Recovery Act (42 USC Sec. 6921; 40 CFR Part 261 App VIII)
  - SARA Superfund Amendments and Reauthorization Act of 1986 Title III Section 302 Extremely Hazardous Substances (42 USC Secs. 11023, 13106; 40 CFR sec. 372.65) and Section 313 Toxic Chemicals (42 USC Secs. 11023, 13106; 40 CFR Sec. 372.65 [as of 6/30/05])
  - TSCA Toxic Substance Control Act (15 U.S.C. s/s 2601 et seq. [1976])
  - SDWA Safe Drinking Water Act (42 U.S.C. s/s 300f et seq. [1974])



Safety Data Sheet (SDS) Revision: 10/31/2018

# **Section 15 - Regulatory Information (continued)**

#### **EPA Regulations (continued):**

Section 313 Supplier Notification: The product, Steel Sheet, Plate, Slab and Coil contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act and 40 CFR part 372:

CAS#	Chemical Name	Percent by Weight
7440-47-3	Chromium	3 max
7439-96-5	Manganese	2.2 max
7440-02-0	Nickel	2.0 max
7440-50-8	Copper	1.0 max

State Regulations: The product, Steel Sheet, Plate, Slab and Coil as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

Pennsylvania Right to Know: Contains regulated material in the following categories:

- Hazardous Substances: Manganese, Molybdenum, Silicon
- Environmental Hazards: Copper, Chromium, Manganese, Nickel
- Special Hazardous Substance: Chromium, Nickel

California Prop.



This product can expose you to chemicals including chromium (hexavalent chromium compounds) and nickel (metallic) which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

New Jersey: Contains regulated material in the following categories:

• Hazardous Substance: Copper, Chromium, Manganese, Nickel

Minnesota: Copper, Chromium, Manganese, Molybdenum, Nickel, Silicon Massachusetts: Copper, Chromium, Manganese, Molybdenum, Nickel

#### Other Regulations:

WHMIS Classification (Canadian): The product, Steel Sheet, Plate, Slab and Coil is not listed as a whole. However individual components are listed.

Ingredients	WHMIS Classification			
Iron	Combustible dusts - Category 1*			
Copper	Acute oral toxicity – oral – Category 4; Combustible dusts*			
Manganese	Reproductive toxicity - Category 2; Specific target organ toxicity - repeated exposure - Category 1; Combustible dusts*			
Molybdenum	Combustible dusts*			
Nickel	Skin sensitization – Category 1; Carcinogenicity – Category 2; Specific target organ toxicity – repeated exposure - Category 1			

<sup>\*</sup>This product could belong to the hazard class "Combustible dust", based on various factors related to the combustibility and explosiveness of its dust, including composition, shape and size of the particles.

#### **Section 16 - Other Information**

Prepared By: AM Health and Safety, Inc.

**Revision History:** 

4/17/10 - Original

06/08/10 - Company update and re-format

12/11/2014 - Reformat to OSHA HAZCOM 2012 SDS

10/31/2018 - Update exposure limits and WHMIS 2015

#### **Additional Information:**

Hazardous Material Identification System (HMIS) Classification

Health Hazard	1
Fire Hazard	0
Physical Hazard	0

HEALTH= 1, Denotes possible chronic hazard if airborne dusts or fumes are generated Irritation or minor reversible injury possible.

FIRE= 0, Materials that will not burn.

PHYSICAL HAZARD= **0**, Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.



Expiration Date: 10/31/2021

 $\mbox{HEALTH} = 1$ , Exposure could cause irritation but only minor residual injury even if no treatment is given.

FLAMMABILITY = 0, Materials that will not burn.

INSTABILITY = 0, Normally stable, even under fire exposure conditions, and are not reactive with water.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.



Safety Data Sheet (SDS) Revision: 10/31/2018

Section 16 - Other Information (continued)						
ABBREVIATIONS/ACRONYMS:						
ACGIH	American Conference of Governmental Industrial Hygienists	NIF	No Information Found			
BEIs	Biological Exposure Indices	NIOSH	National Institute for Occupational Safety and Health			
CAS	Chemical Abstracts Service	NTP	National Toxicology Program			
CERCLA	CERCLA Comprehensive Environmental Response, Compensation, and Liability Act		Organization Resources Counselors			
CFR	Code of Federal Regulations	OSHA	Occupational Safety and Health Administration			
CNS	Central Nervous System	PEL	Permissible Exposure Limit			
GI, GIT	Gastro-Intestinal, Gastro-Intestinal Tract	PNOR	Particulate Not Otherwise Regulated			
HMIS	Hazardous Materials Identification System	PNOC	Particulate Not Otherwise Classified			
IARC	International Agency for Research on Cancer	PPE	Personal Protective Equipment			
LC50	Median Lethal Concentration	ppm	parts per million			
LD50	Median Lethal Dose	RCRA	Resource Conservation and Recovery Act			
LD Lo	Lowest Dose to have killed animals or humans	RTECS	Registry of Toxic Effects of Chemical Substances			
LEL	Lower Explosive Limit	SARA	Superfund Amendment and Reauthorization Act			
LOEL	Lowest Observed Effect Level	SCBA	Self-contained Breathing Apparatus			
LOAEC	Lowest Observable Adverse Effect Concentration	SDS	Safety Data Sheet			
μg/m³	microgram per cubic meter of air	STEL	Short-term Exposure Limit			
mg/m <sup>3</sup>	milligram per cubic meter of air	TLV	Threshold Limit Value			
mppcf	million particles per cubic foot	TWA	Time-weighted Average			
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit			
NFPA	National Fire Protection Association					

**Disclaimer:** This information is taken from sources or based upon data believed to be reliable. However, SSAB Americas and AM Health and Safety, Inc. make no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.